Model 1026

Provides a variety of functions: megohmmeter, DC voltmeter, **AC voltmeter, ohmmeter and** continuity testing

► SPECIFICATIONS

MODEL	1026
INSULATION TESTS	
Test Voltage 250V 500V 1000V	1kΩ to 4000MΩ 1kΩ to 4000MΩ 1kΩ to 4000MΩ
$ \begin{array}{ll} \textbf{Accuracy} & <2000 \text{M}\Omega \\ \geq & 2000 \text{M}\Omega \end{array} $	±3% of Reading + 5cts ±5% of Reading + 5cts
RESISTANCE TESTS	
Measurement Range	Auto ranging to 4000Ω
Resolution	0.1 to 1Ω
Accuracy	±1% of Reading + 5cts
CONTINUITY TESTS	
Measurement Range	Displays and beeps below 40Ω
Active	≤40Ω
Protection	600Vrms
VOLTAGE TESTS	
AC VOLTAGE Measurement Range	0 to 600V
Accuracy	±1.5% of Reading + 5cts
DC VOLTAGE Measurement Range	0 to 600V
Accuracy	±1% of Reading + 3cts
ELECTRICAL	
Power Source	Eight 1.5V AA Alkaline batteries (included)

▶ PRODUCT INCLUDES

Test leads, alligator clips, batteries, soft carrying case and user manual.













► FEATURES

- · Test voltage selections of 250V, 500V and 1000V
- Insulation measurements to 4000MΩ
- Resistance measurements to 4000Ω
- Continuity test
- · Continuity beeper
- 600VAC/DC test voltage range
- Large, easy-to-read digital display
- Data hold switch
- Test button may be "locked-on" for three minutes for hands-free operation
- Automatic discharge when test button is released
- Low battery indicator
- Includes test leads and soft carrying case
- EN 61010-1, 1000V CAT II, 600V CAT III

CATALOG NO. DESCRIPTION

Megohmmeter Model 1026 (Digital, 250V, 500V, 1000V, 4000 Ω , V) 2117.72

