Models 1035 & 1039

For voice, data and video cable applications

FEATURES

- True Megohmmeter[®]
- Test voltage combinations of 250V, 500V and 1000V
- Insulation measurements to $2000M\Omega$ (2G Ω)
- Automatic test inhibition (if live sample >25V)
- Automatic discharge for operator safety
- Multi-line, 4000-count, backlit, digital display with analog bargraph
- Resistance measurements to $400 \text{k}\Omega$
- Continuity with 200mA test current
- Timer function for easy DAR and PI (Model 1045)
- Slip-proof, over-molded, protective rubber housing for rugged field use
- Includes test leads and soft carrying case
- Test voltage combinations of 50V, 100V, 250V and 500V (Model 1035)
- Insulation measurement to 20,000MΩ (20GΩ) (Model 1035)
- Insulation measurement to 400MΩ (Model 1039)
- Capacitance measurement to 4000nF (Model 1039)
- Cable length measurement to 80.0km (>264,000 ft) (Model 1039)
- Ideal for telecom testing and high sensitivity measurements
- Backlit display (Models 1035, 1039, 1040 & 1045)



► SPECIFICATIONS

MODELS		1035	1039	
		1035	1039	
INSULATION TESTS	5			
Test Voltage	50V	10k Ω to 2000M Ω (2G Ω)	10k Ω to 400M Ω	
	100V	20k Ω to 2000M Ω (2G Ω)	20k Ω to 400M Ω	
	250V	50k Ω to 20,000M Ω (20G Ω)	_	
	500V	100k Ω to 20,000M Ω (20G Ω)	-	
Open Circuit Voltage		<75V @ 50V, <150V @ 100V, <375V @ 250V, <750V @ 500V		
Short Circuit Current		≤3mA		
Accuracy		$\pm 3\%$ of Reading ± 5 cts		
Voltage Test/Safety C	heck	0 to 600Vac/bc		
Voltage Warning India	cator	>25V		
Test Inhibition		Yes >25V		
RESISTANCE TEST	S			
Measurement Range		0.0 to 400k Ω	0.0 to 40.0kΩ	
Test Voltage		7 to 9V	7 to 9V	
Test Current		$600\mu A < 400\Omega; 6\mu A > 40\Omega$	600μA < 400Ω	
Accuracy >40	J0kΩ	$\pm 3\%$ of Reading ± 1 ct	$\pm 3\%$ of Reading ± 1 ct	
CURRENT TESTS				
AC/DC Current Range		-	0.00 to 400mA (240A) (with probe option)	
CAPACITANCE/CAB	BLE LE	NGTH		
Capacitance Range		_	0.00 to 4000nF	
Cable Length Range		-	0.000 to 80.0km	
VOLTAGE TESTS				
Measurement Range		_	0 to 400Vac	
Accuracy		_	$\pm 3\%$ of Reading ± 1 ct	
ELECTRICAL				
Power Source	ver Source Six 1.5V AA Alkaline batteries (included)			

CATALOG NO. DESCRIPTION

2116.89	Megohmmeter Model 1030 (Digital w/Analog Bargraph, 250V, 500V)	
2116.92	Megohmmeter Model 1040 (Digital w/Analog Bargraph, Alarm, Backlight, 500V, 1000V, 400k Ω , Continuity)	
2116.93	Megohmmeter Model 1045 (Digital w/Analog Bargraph, Alarm, Timer, Backlight, 250V, 500V, 1000V, 400kΩ, Continuity)	
2117.30	Megohmmeter Model 1040 Field Kit (Model 1040, Remote Test Probe & Field Case)	
2117.31	Megohmmeter Model 1045 Field Kit (Model 1045, Remote Test Probe & Field Case)	
2116.90	Megohmmeter Model 1035 (Digital w/Analog Bargraph, Alarm, Backlight, 50V, 100V, 250V, 500V, 400k Ω)	
2116.91	Megohmmeter Model 1039 (Digital w/Analog Bargraph, Alarm, Timer, ∆Rel, Backlight, 50V, 100V, mA, nF, km)	
2115.42	Megohmmeter Model 1035 Field Kit (Model 1035, Remote Test Probe & Field Case)	
Accessories	(Optional)	
2118.97	Remote Test Probe	
2118.98	Field Case (Waterproof)	
2118.99	Hands-Free Carrying Case	

CALRIGH I INSTRUMENTS The Right Source For Your Test & Measurement Needs

8715 Mesa Point Terrace San Diego, CA 92154 Toll Free: 1.866.363.6634 Tel: 1.619.429.4545 Fax: 1.619.374.7012 Email: sales@calright.com http://www.calright.com