

**Model CA832**

**Designed to assess sound ambiences or nuisances in accordance with international safety and quality standards**



**SPECIFICATIONS**


MODEL	CA832
<b>MEASUREMENTS</b>	
Measurement Range	37 to 80dB 50 to 100dB 80 to 130dB
Measurement Rate	2.5 times per second
Dynamic Range	50db
Frequency Range	31.5 to 8000Hz
Accuracy	±1.5dB (ref. 94dB@1kHz)
Resolution	0.1dB
Precision	±2.0dB
Display	2000-count
Sensor Type	0.5" (13mm) electric (prepolarized) condenser microphone True RMS measurement with independent frequency weighting
Applicable Standard	IEC 651 type 2/ANSI S 1.4 type 2/JIS C 1502
Auxiliary Output	DC output: 10mV/dB – 50Ω AC output: 1.0Vrms – 600Ω
Frequency Weighting	Curves A and C
Time Weighting	S (slow) and F (fast)
<b>GENERAL</b>	
Display	3½ digit liquid crystal display (LCD), 2000-count
Operating Temperature	32° to 122°F (0° to 50°C), 80% RH without condensation
Storage Temperature	-4° to 140°F (-20° to 60°C), 0 to 80% RH without battery
Power Source	One 9V Alkaline battery (included)
Low Battery Indication	is displayed when battery voltage is low
Dimensions	9.33 x 2.38 x 1.5" (237 x 60.5 x 38mm)
Weight	8.11oz (230g) including battery

**FEATURES**

- Easy one-hand operation
- Measures sound according to the sensitivity of the human ear
- Max function
- Three measurement ranges from 37 to 130dB
- Accuracy ±1.5dB (ref. 94dB@1kHz)
- Two time weighting curves: S (slow) - 550ms and F (fast) – 55ms
- Two frequency weighting curves: A and C
- Auxiliary output for recording
- Tripod mountable
- 2000-count backlit LCD
- Lightweight and compact
- Includes rugged, shockproof, protective and dirt resistant gray cover

**APPLICATIONS**

- Factories
- Schools and Libraries
- Airports
- Office environments and Studios
- Auditoriums
- Hospitals



*Tripod mounting screw allows for mounting on a standard tripod stand. (Tripod not included)*

**PRODUCT INCLUDES**

*Shockproof holster, protective foam microphone cap, screwdriver, male jack connector, assembly screw for camera type tripod, 9V battery and user manual.*

CATALOG NO.	DESCRIPTION
-------------	-------------

2121.23 Sound Level Meter Model CA832



*The Right Source For Your Test & Measurement Needs*

8715 Mesa Point Terrace San Diego, CA 92154  
Toll Free: 1.866.363.6634 Tel: 1.619.429.4545 Fax: 1.619.374.7012  
Email: sales@calright.com <http://www.calright.com>