Special product features

ENVIRONMENTAL TESTERS

Thermo-Hygrometer













Discover how to maintain an appropriate humidity level





 ϵ

►SPECIFICATIONS

MODEL	CA846
MEASUREMENTS — TEMPERATURE	
Measurement Range	-4° to 140°F (-20° to 60°C)
Display Resolution	0.1°F (0.1°C)
Sensor	NTC Temperature Sensor
Accuracy	-4° to 32°F: ±2°F (-20° to 0°C: ±1°C) 32° to 140°F: ±1°F (0° to 60°C: ±0.5°C)
MEASUREMENTS — RELATIVE HUMIDITY	
Measurement Range	0 to 100% RH
Display Resolution	0.1% RH
Sensor	Capacitive Humidity Sensor
Accuracy	±5.0%, 25°C, 10% to 90% RH ±10.0%, 25°C, 0% to 10% RH, 90% to 100% RH
GENERAL	
Display	3½ digit liquid crystal display (LCD), 2000-count
Operating Temperature	32° to 122°F (0° to 50°C), 80% RH
Storage Temperature	-4° to 140°F (-20° to 60°C), 0 to 80% RH without battery
Polarity	Automatic
Power Source	One 9V Alkaline battery (included)
Low Battery Indication	= +1 is displayed when battery voltage is low
Dimensions	6.81 x 2.38 x 1.5" (173 x 60.5 x 38mm)
Weight	Approx. 7oz (197g) including battery

► FEATURES

- · Easy one-hand operation
- Measures temperature in °F and °C
- Accurate NTC sensor
- · Quick response RH sensor
- · Max and Hold functions
- 2000-count backlit LCD
- Lightweight and compact
- Removable protective sensor cover
- Includes rugged, shockproof, protective and dirt resistant gray cover

►APPLICATIONS

- Greenhouses
- · HVAC installation and maintenance
- · Office environments
- Labs
- Environmental studies
- Weather monitoring
- · Food distribution and storage
- Blood banks

CATALOG NO. DESCRIPTION

