

## 5 MHz DDS Function Generator Model 4005DDS



The B&K Precision model 4005DDS is a versatile 5 MHz DDS (direct digital synthesis) function generator with a 4-digit display. The instrument generates sinusoidal, triangular, and square waveforms over the 1 Hz to 5 MHz range. The output voltage can be varied from 0 to 10 Vp-p into 50 ohms or to 20 Vp-p into open circuit. A continuously variable DC offset allows the output to be injected directly into circuits at the correct bias level. These features make the 4005DDS great for education and other applications that need basic waveform generation.

### Features and Benefits

- Frequency is selectable from 1 Hz to 5 MHz
- Sine, square, or triangle waveform output
- Direct digital synthesis (DDS) architecture
- Bright, easy-to-read LED display
- Number pad for quick input of frequency
- Front panel push button and pull knob can attenuate output by up to 40 dB



Kensington security slot helps secure your function generator and prevents theft.



Model	4005DDS
<b>Frequency Characteristics</b>	
Waveforms	Sine, Square, Triangle
Range	1 Hz to 5 MHz
Resolution	4 digits or 1 Hz
Accuracy	0.02% (200 ppm)*
<b>Output Characteristics</b>	
Impedance	50 Ω ± 2%
Amplitude Range	Variable control from 20 mVpp to 20 Vpp (open circuit); 10 mVpp to 10 Vpp (into 50 Ω)
Attenuation	-20 dB ± 2%, -40 dB ± 2%
DC Offset	Variable ± 10 V (open circuit); ± 5 V (into 50 Ω)
Duty Cycle	Adjustable 20% - 80% to 3 MHz for square
<b>Sine Wave</b>	
Harmonic Distortion	-50 dBc, DC to 20 kHz -30 dBc, 20 kHz to 5 MHz
Flatness	± 0.3 dB to 1 MHz, ± 1 dB to 5 MHz
<b>Square Wave</b>	
Symmetry	± 2% to 100 kHz, ± 5% to 5 MHz
Rise Time	≤ 35 ns
<b>Triangle Wave</b>	
Linearity	≥ 98% to 100 kHz, ≥ 95% to 5 MHz
<b>SYNC Output</b>	
Level	≥ 3 V
Rise Time	≤ 25 ns
<b>General</b>	
AC Input	115/230 VAC, 50/60 Hz
Operating Temperature	32 °F to 104 °F (0 °C to 40 °C)
Humidity	10% - 80% R.H.
Storage Temperature	-4 °F to 158 °F (-20 °C to 70 °C)
Storage Humidity	0% - 90% R.H.
Dimensions (W x H x D)	11" x 4" x 11.7" (279.4 x 101.6 x 297.2 mm)
Weight	5.05 lbs (2.3 kg)
<b>One-Year Warranty</b>	
Included Accessories	Instruction manual, power cord, BNC to BNC cable, BNC to alligator clips

\*Applies to frequencies ≥ 1 kHz.

Note: All specifications apply to the unit after a temperature stabilization time of 15 minutes. Specifications and information are subject to change without notice.

Technical data subject to change  
© B&K Precision Corp. 2014  
v042114

[www.bkprecision.com](http://www.bkprecision.com)



**CALRIGHT INSTRUMENTS**  
The Right Source For Your Test & Measurement Needs

8715 Mesa Point Terrace San Diego, CA 92154  
Toll Free: 1.866.363.6634 Tel: 1.619.429.4545 Fax: 1.619.374.7012  
Email: [sales@calright.com](mailto:sales@calright.com) <http://www.calright.com>