

## 5 MHz Sweep Function Generator Model 4012A



Model 4012A is a popular 5 MHz generator for general bench and lab use with an ideal mixture of features and sweep function at a compelling price.

### Features & Benefits

- 0.5 Hz to 5 MHz
- Sine, Square, Triangle, Pulse, and Ramp output
- Coarse and fine tuning knobs
- 4-digit LED display
- Linear and log sweep
- Variable duty cycle
- Variable DC offset
- Variable 20 Vpp output into open circuit (10 Vpp into 50  $\Omega$ )

Specifications	4012A
<b>Frequency Characteristics</b>	
Waveforms	Sine, Square, Triangle, $\pm$ Pulse, $\pm$ Ramp
Range	0.5 Hz to 5 MHz in 7 ranges
Resolution	4 digits
Tuning Range	10:1
Fine	$\pm$ 5% of coarse setting
Variable Duty Cycle	15:85:15 cont variable
Operating Modes	Normal, Sweep, VCG
<b>Output Characteristics</b>	
Impedance	50 $\Omega$ $\pm$ 10%
Level	20 V p-p Open circuit, 10 V p-p into 50 $\Omega$
Amplitude	Variable, 20 dB range typical
Attenuation	-20 dB $\pm$ 1dB
DC Offset	Preset: $\pm$ 0.1 V typical Variable: $\pm$ 10 V open-circuit $\pm$ 5 into 50 $\Omega$
<b>Sine Wave</b>	
Distortion	<3% typical at 1 kHz
Flatness (Into 50 $\Omega$ )	$\pm$ 5% $\pm$ (.45 dB) 0.5 Hz to 5 MHz
<b>Square Wave</b>	
Symmetry	0.1 Hz to 100 kHz <2%
Rise time (Into 50 $\Omega$ )	$\leq$ 120 nS
<b>Triangle Wave</b>	
Linearity	$\geq$ 98% to 100 kHz
<b>TTL Output</b>	
Level	0.8 V to 2.4 V
Rise time	$\leq$ 20 nS
Duty Cycle	50% typical
<b>CMOS Output</b>	
Max. Frequency	2 MHz
Level	4 V to 14 V $\pm$ 0.5 V p-p continuously variable
Rise Time	$\leq$ 120 nS (Open circuit)
<b>VCG (Voltage controlled generator)</b>	
Input Voltage	0-10 V $\pm$ 1 V causes a 100:1 frequency change
Impedance	10 k $\Omega$ $\pm$ 5%
<b>Sweep Operation</b>	
Mode	LIN/LOG
Width	100:1 continuously variable
Rate	0.5 s to 30 s continuously variable
<b>Frequency Counter</b>	
Accuracy	Time base accuracy $\pm$ 1 count
Time Base Accuracy	$\pm$ 10 ppm (23 $^{\circ}$ C $\pm$ 5 $^{\circ}$ C)
Display	4 digit LED
<b>General</b>	
AC Input	120/230 VAC $\pm$ 10%, 50/60 Hz, internal jumper selectable
Dimensions (W x H x D)	10.5" x 4.5" x 12.25" (266.7 x 114.3 x 311.15 mm)
Weight	4 lbs (1.8 kg)
<b>Two-Year Warranty</b>	
Included Accessories	Instruction manual, output cable (BNC to alligator clips)

Technical data subject to change  
© B&K Precision Corp. 2014  
v080114

[www.bkprecision.com](http://www.bkprecision.com)



**CALRIGHT  
INSTRUMENTS**  
*The Right Source For Your Test & Measurement Needs*

8715 Mesa Point Terrace San Diego, CA 92154  
Toll Free: 1.866.363.6634 Tel: 1.619.429.4545 Fax: 1.619.374.7012  
Email: [sales@calright.com](mailto:sales@calright.com) <http://www.calright.com>