

Insulation Testers (Megohmmeters)

These insulation testers are intended primarily for periodic testing of industrial motors, transformers, electrical wiring, and cable insulation for signs of deterioration. Low readings may indicate impending failure and permit replacement during routine maintenance rather than risking production downtime. Also useful for safety testing of TV sets and appliances to assure no hazardous leakage current. The voltage and resistance ratings for insulation testing are often specified for the product to be tested.



300



305

Models 300, 305

- Test insulation resistance
- Measure AC voltage to 600V
- Battery powered
- 1000V, 2000MΩ (Model 300)
- 500V, 1000MΩ (Model 305)

Models 307, 308

- Selectable 250V, 500V, or 1000V insulation test
- Low resistance test
- Extra rugged integral carrying case
- Live circuit indicator warns of safety hazard
- Push to test

Specifications

	models			
	300	305	307	308
Type	Analog	Analog	Analog	Digital
Output Voltage	1000VDC	500VDC	1000VDC	1000VDC
Maximum current	250μA	500μA	2mA	1.2mA
Resistance Range	1MΩ - 2000MΩ	0.2MΩ - 1000 MΩ	1000V 0-200MΩ 500V 0-100MΩ 250V 0-50MΩ	0-2000MΩ 0-2000MΩ 0-2000MΩ
Center Scale	50MΩ	20MΩ	1MΩ, 2MΩ, 4MΩ	Does not apply
Accuracy				250V 500V 1000V
		Infinity: within 1% of scale length		0-100Ω ±(1.5%+3D) ±(1.5%+2D)
		Zero: within 1% of scale length		100-200MΩ ±(2%+5D) ±(1.5%+2D) ±(1.5%+2D)
		All points ±5% of reading		200-1700MΩ ±(3%+7D) ±(3%+4D) ±(3%+3D)
				1700-2000MΩ ±(4%+8D) ±(4%+6D) ±(4%+5D)
AC Voltage Test				
Range	0 to 600 VDC			Live Circuit Indicator
Frequency Response	10Hz to 100kHz			
Accuracy	±4% of full scale			
Low resistance Test	Does not apply		0-50Ω	0-200Ω
Accuracy	Does not apply		±5% of reading	±(1.5% + 2 digits)
General Specifications				
Power Requirements	Six "AA" cells (supplied)			Eight "AA" cells (supplied)
Battery Life	4 hours typical alkaline		12 hours continuous	10 hours continuous w/alkaline
Operating Temperature	32° to 122°F (0° to 50°C), ≤ 70% RH			
Storage Temperature	-4° to 140°F (-20° to 60°C), <80% RH (with batteries removed)			
Dimensions	6.66 x 4.18 x 1.42" (169 x 106 x 36mm)		7 x 8.5 x 3.5" (180 x 220 x 90mm)	
Weight	15oz. (430g) w/batteries		2.6 lb (925g) with batteries	

Accessories

One Year Warranty

Supplied: Batteries, Carrying Case, Test Leads, Instruction Manual

Batteries, Integral Carrying Case w/strap, Test Lead, Instruction Manual



The Right Source For Your Test & Measurement Needs

2222 Verus Street Suite C San Diego CA 92154 USA
 Toll Free: 866.363.6634 Tel: 619.429.4545 Fax: 619.374.7012
 Email: sales@calright.com http://www.calright.com