

# Hipot Function Tester

**HTT-1**

FAST

SAFE

RELIABLE



## HIPOT & GROUND CONTINUITY FUNCTION TESTER

Designed to provide a fast, safe and reliable method of testing all Hipot and Ground Continuity test equipment. Saves quality assurance and manufacturing personnel time and reduces the potentially dangerous risks associated with other testing methods.

### Features

- Quickly and easy proves function of any Hipot and Ground Continuity Tester, including High Current models delivering up to 30 amps.
- Provide compliance to:
  - CCA-201 Sections: 5.4 Quality Control & Production Verification Test 7.2 Functional Test.
  - CCA-202 MC6-C Inspection form section C3.4
  - CCA-204 section B.6.2
- Verifies operation of your test equipment before each shift or before testing of large production runs, ensuring quality standards are being met.
- Simulates Ground Continuity passing/failing, Leakage Current passing/failing conditions and Dielectric Withstand passing/failing conditions.
- ARC view window allows visual verification of the Hipot breakdown/failure.
- Custom configuration allow you to specify your required Dielectric withstand voltage failure level.
- Portable, lightweight. Measures 5.3 x 6.8 x 2.3 inches.
- No batteries or power required – operates from voltage generated by tester.
- Simple to set-up and operate.
- Ergonomically designed for safety, speed and efficiency.
- 3 switches for enabling verification tests.
- Custom test leads available.
- One year warranty.

**CALRIGHT  
INSTRUMENTS**

*The Right Source For Your Test & Measurement Needs*

8715 Mesa Point Terrace San Diego, CA 92154  
Toll Free: 1.866.363.6634 Tel: 1.619.429.4545 Fax: 1.619.374.7012  
Email: [sales@calright.com](mailto:sales@calright.com) <http://www.calright.com>

# HTT-1

↘ FAST

↘ SAFE

↘ RELIABLE

## ↘ Specifications

Maximum Current capability of Ground test circuit:	30 Amps
Setting of PASS for Ground Circuit:	0 ohm
Setting of FAIL for Ground Circuit:	Open
Setting of PASS for Leakage Current:	Open Circuit
Setting of FAIL for Leakage Current:	Short Circuit
Maximum voltage capability of Hipot test circuit:	3000Vac / 4200Vdc
Setting of PASS for Ground Circuit:	Open circuit
Setting of FAIL for Ground Circuit:	Arc-over at 750V ± 400Vac / 1050V ± 560Vdc.

## ↘ Environmental

Operation Temperature:	15 - 40 °C
Relative Humidity Range:	0 - 90 % Non-Condensing

## ↘ General

Dimensions:	5.3 in Wide x 6.8 in High x 2.3 in Deep
Weight:	2 lbs
Product Package:	HTT-1 HTT-1 Product Manual 18 AWG Test Lead (Black) NIST Traceable Calibration Certificate to MIL-STD45662-A