

Passive Component LCR Meter

Measures Inductance, Capacitance, and Resistance

With secondary parameter Q (Quality), D (Dissipation), R (Resistance), θ (Phase), ESR (Equivalent Series Resistance)

Features:

- Simultaneous 20,000/2,000 count backlit display of the primary parameter (L, C or R) with the secondary parameter of Q (quality), D (dissipation) R (resistance), θ (phase), or ESR (equivalent series resistance)
- Auto Select measurement function with 1kHz default test frequency
- Five test frequencies
- Set Hi/Lo limits using absolute values or percentage limits
- Relative mode function
- Parallel or Series equivalent circuit
- Auto power off with disable
- Low battery and overrange indicators
- Built-in test fixture or use external test leads
- Built-in RS-232 interface
- Open and Short calibration removes unwanted stray impedances from the measurement
- Complete with test leads, 9V battery, and carrying case
- Optional SMD Tweezer (LCR203) and plug-in SMD Component Fixture (LCR205)



LCR205 SMD Component Fixture

Specifications	Ranges	Basic Accuracy
Inductance	20 μ H, 200 μ H, 2000.0 μ H, 20.000mH, 200.00mH 2000.0H, 20.000H, 200.00H, 2000.0H	\pm (0.5%rdg + 5 digits) (DF<0.1)
Capacitance	20pF, 200pF, 2000pF, 20.000nF, 200.00nF, 2000.0nF 20.000 μ F, 200.00 μ F, 2.0000mF, 20.00mF	\pm (0.5%rdg + 5 digits) (DF<0.1)
Resistance	20.00 Ω , 200.00 Ω , 2.0000k Ω , 20.000k Ω , 200.00k Ω , 2.0000M Ω , 20.000M Ω , 200.0M Ω	\pm (0.5%rdg + 5 digits)
DF (with C)	0.000 to 999	
Q	0.000 to 999	
Phase	\pm 90°	
Test Frequency	100Hz/120Hz/1kHz/10kHz/100kHz	
Dimensions	7.6 x 3.5 x 1.6" (193 x 88 x 41mm)	
Weight	14.8oz (420g)	

Ordering Information:

- LCR200Passive Component LCR Meter
 LCR203SMD Tweezer for Model LCR200
 LCR205SMD Component Fixture For Model LCR200
 153117120V AC Adaptor
 153230220V AC Adaptor