



1000A 3-Phase Power Analyzer/Datalogger

Four clamps with simultaneous display On single phase, 3-phase/3-wire or 3-phase/4-wire systems

Features:

- Large backlighting LCD displays 10 parameters simultaneously (kW , kVAR, kVA, PF plus the voltage and current of the 3 phases)
- Up to four current probes can be connected to the analyzer
- Clamp-on True RMS power measur ements with software for Harmonics analysis
- Displays Active Power (kW), Apparent Power (kV A), Reactive Power (kVAR) and Power Factor
- Current measurements to 1000A and Voltage measurements to 600V
- kWH, kVARh and kVAh energy measurements
- Automatically logs up to 20,000 sets of measur ements and manually logs up to 99 sets
- Programmable Start/Stop datalogging times
- PC interface with Windows
 95/98/NT/2000/ME/XP compatible software for single and three phase voltage/current Waveform display and Harmonic analysis
- Phase sequence measurements
- · Auto power off with disable feature
- CAT III-1000V, UL Listed; CE approved; 1yr warranty

Applications:

- AC Power Quality Evaluation
- Harmonic Analysis
- Motor/Generator Installation
- Energy Audits
- Ordering Information:




The Right Source For Your Test & Measurement Needs






leads with alligator clips, 8 AA batteries, AC

adaptor, software, PC interface cable, and case



Software included to download, store data, and display on a PC



Software included for Harmonics Analysis

Specifications	Range	Basic Accuracy
ACV (True rms)	999.9V	±(0.5%rdg+10d)
ACA	1000A	±(2%rdg+20d)
Active Power (kW)	999.9kW	±(1.5%rdg+20d)
Apparent Power (kVA)	999.9kVA	\pm (1.5%rdg+20d)
Reactive Power (kVAR)	999.9kVAR	±(1.5%rdg+20d)
Power Factor	-1.000 to +1.000	±(3%rdg+30d)
Frequency	60Hz to 100Hz	$\pm (0.5\% rdg + 1d)$
Phase	+90.0°~ 11°~ -90.0°	$\pm (3^{\circ} + 30d)$
Active Power Energy (kWh)	0.0kWh to 119.3MWh	±(1.5%rdg+20d)
Apparent Power Energy (kVAh)	0.0kVAh to 119.3MVAh	\pm (1.5%rdg+20d)
Reactive Power Energy (kVARh)	0.0kVARh to 119.3MVARh	±(1.5%rdg+20d)
Harmonics	1 to 31 (with the software)	±(1.5%rdg+20d)
Datalogging	20,000 reading	
Dimensions	9.25 x 4.5 x 2.1" (235 x 116 x 54mm)	
Weight	Meter: 25.8oz (730g); Clamp: 11.8oz (333g)	

2222 Verus Street Suite C San Diego CA 92154 USA Toll Free: 866.363.6634 Tel: 619.429.4545 Fax: 619.374.7012 Email: sales@calright.com http://www.calright.com