


Fruit Hardness Tester

 Penetrometer measures fruit ripeness to improve fruit quality, harvest, storage, and product transportation time

Features:

- Four Penetrometer tips for large/hard and small/soft fruits
- Basic accuracy of 0.5%
- Tension or Compression, Peak hold and Zero functions
- Positive/Reverse display for easy readability
- Large LCD with back light feature
- RS-232 PC interface
- Optional software available (407001)
- Complete with four (3mm, 5mm, 8mm, 11mm) Penetrometer Tips, six AA 1.5V batteries, and hard carrying case



Complete with four (3mm, 5mm, 8mm, 11mm) Penetrometer Tips, six AA 1.5V batteries, and hard carrying case

Specifications	
Range	44.10lbs, 20kg, 196.10 Newtons
Accuracy	±(0.5% + 2 digits)
Resolution:	0.01lbs, 0.01kg, 0.05 Newtons
Minimum Display	0.07lbs, 0.02kg, 0.3 Newtons
Display:	5 digits, 0.63" (16mm) LCD display
Update Rate:	Fast mode 0.2 secs; Slow mode 0.6 secs.
Full scale deflection:	approx 0.4mm
Transducer type:	Load cell
Peak Hold:	Freezes Max reading on display
Power Supply:	Six 1.5V AA batteries
Weight:	1.4 lbs (650g)
Size:	8.5 x 3.5 x 1.8" (215 x 90 x 45mm)

Ordering Information:

FHT200.....Fruit Hardness Tester
407001.....Data Acquisition program and cable
407001-USB.....USB adaptor for 407001
153117.....117V AC adaptor
UA100-240.....100 to 240V AC adaptor with 3 plugs (US, EU, UK)