



# ALL WITH **ONE.**

From plumbers to architects, the FLIR ONE® Pro is perfect for all professionals that need a little help on the job site.

## Features:

- MSX™
- Ruggedized Design
- OneFit™ Adjustable Connector
- VividIR™ Advanced Image Processing
- Higher Resolution Thermal Sensor
- Advanced Diagnostics
- One-Touch Reporting
- Enhanced FLIR ONE App



*The Right Source For Your Test & Measurement Needs*



## FLIR **ONE**®

8715 Mesa Point Terrace San Diego, CA 92154  
Toll Free: 1.866.363.6634 Tel: 1.619.429.4545 Fax: 1.619.374.7012  
Email: [sales@calright.com](mailto:sales@calright.com) <http://www.calright.com>

**General**

Certifications	MFi (iOS version), RoHS, CE/FCC, CEC-BC, EN61233
Operating temperature	0 °C – 35 °C, battery charging 0 °C – 30 °C
Non-operating temperature	-20 °C – 60 °C
Size	68mm W x34mm H x14mm D
Weight	36.5g
Mechanical shock	Drop from 1.8m

**Video**

Thermal and visual cameras with MSX	
Thermal sensor	Pixel size 12um (Con), 8 – 14 um spectral range
Thermal resolution	160x120
Visual resolution	1440x1080
HFOV / VFOV	55° ± 1° / 43° ± 1° (Pro)
Frame rate	8.7Hz
Focus	Fixed 15cm – Infinity

**Radiometry**

Scene dynamic range	-20 °C – 400 °C
Accuracy	±3°C or ±5%, typical Percent of the difference between ambient and scene temperature. Applicable 60s after start-up when the unit is within 15 °C – 35 °C and the scene is within 5 °C – 120 °C.
Thermal sensitivity (MRDT)	150mK
Emissivity settings	Matte: 95%, Semi-Matte: 80%, Semi-Glossy: 60%, Glossy: 30% Reflected background temperature is 22°C
Shutter	Automatic/Manual

**Power**

Battery life	1h
Battery charge time	40min

**Interfaces**

Video	Male Lightning (iOS), Male micro USB-C (Android)
Charging	Female micro USB-C (5V/1A)

**App**

Video and still image display/capture	Saved as 1440x1080
File formats	Still images – radiometric jpeg Video – MPEG-4 (file format MOV (iOS), MP4 (Android))
Capture modes	Video, Still image, Time lapse and Panorama
Palettes	Gray (white hot), Hottest, Coldest, Iron, Rainbow, Contrast, Arctic, Lava and Wheel.
Spot meter	Off / °C / °F. Resolution 0.1°C / 0.1°F
Adjustable MSX distance	0.3m – Infinity
Battery charge monitor	0 – 100%