

GENERAL[®]

Non-penetrating LCD Moisture Meter w/ Tricolor Bar Graph

**Ideal for DIY enthusiasts, woodworkers, contractors,
building inspectors and water damage remediators**

Features & Benefits:

- Separate settings for drywall, masonry, softwood and hardwood
- 2 in. (50mm) diagonal backlit LCD + 3-color LED bar graph
- Non-invasive, non-marring, technically ideal for detecting moisture under finished surface
- 3/4 in. (20mm) maximum sensing depth
- $\pm 4\%$ accuracy on wood
- Reading HOLD button
- Auto power off function and out-of-range alarm
- Low battery indication
- Powered by one "9V" battery



Detect potential moisture problems without making pinholes. Save time, money and hassles.



No. MMD7NP



Non-penetrating LCD Moisture Meter w/ Tricolor Bar Graph

Specifications:

Measurement Range:

0 to 53% for hardwood;
0 to 35% for softwood;
relative readings for wallboard
and masonry

Measurement Accuracy:

±4% for hardwood and softwood

Inductive Sensor Depth:

1.5 x 1.5 in. (38 x 38mm)

Maximum Sensing Depth:

3/4 in. (20mm)

Alarm Levels:

>18% for wood;
>70% for drywall and masonry

LCD Size:

2 in. (50mm) diagonal with three
0.5 in. (13mm) high digits

Bar Graph Composition:

3 each green, yellow and red LEDs

LED Bands:

For wood:

green = 0 to 30%
yellow = 31 to 70%
red = >70%

For drywall and masonry:

green = 5 to 13%
yellow = 15 to 17%
red = >18%

Auto Power Off Trigger:

2 minutes of inactivity

Operating Temperature:

32° to 104°F (0° to 40°C)
@ 5 to 95% RH

Storage Temperature:

14° to 122°F (-10° to 50°C)

Power Source:

1 "9V" battery

Dimensions:

6.7 x 2.9 x 1.2 in.
(170 x 75 x 30mm)

Weight:

5.4 oz. (152g) without battery

Includes:

1 "9V" Battery, User's Manual and
1 Year Warranty



No. MMD7NP



Wet drywall behind removed
bathtub tiles



Hardwood boards entering a kiln
that will dry them to a moisture
content of less than 10%



Locate moisture or
water damage



The Right Source For Your Test & Measurement Needs

2222 Verus Street Suite C San Diego CA 92154 USA

Toll Free: 866.363.6634 Tel: 619.429.4545 Fax: 619.374.7012

Email: sales@calright.com <http://www.calright.com>