

REED

THE RIGHT SOURCE THE RIGHT SOLUTIONS

REFRIGERANT LEAK DETECTOR

TECHNICAL DATA

FEATURES

- Detects and pinpoints even small leaks of refrigerant gases
- Semiconductor gas sensor
- Detects all halogenated refrigerants
- Quickly and accurately mark any leak spot
- Microprocessor control with advanced digital signal processing
- Audible and visual leak indications
- Instantaneous response time
- No user calibration required
- Includes reference leak source, batteries and carrying case

SPECIFICATIONS

Gases Sensed: CFCs: R11, R12, R13; HCFCs: R22, R502, R500; HFCs: R134a, R123, R125, R23, R404A, R407C, R410A and other halogen based compounds

Sensitivity: R22, 134a: Hi 6g/year, L: 30g/year
R404A, 407C, 410A: Hi 8g/year, L: 40g/year

Alarm Settings: Buzzer, Tricolour LED bar indicator

Sensor: Advanced ionization detection

Response Time: Less than 1 second

Warm-up Time: 10 seconds

Power Supply: 4 x "AA" batteries

Battery Life: Approx. 40 hours continuous use

Probe: 390mm (15") flexible stainless probe

Dimensions: 6.8 x 2.6 x 2.2" (173 x 66 x 56mm)

Weight: 9.3 oz (265g)



ORDERING INFORMATION

C-380 Refrigerant Leak Detector
R-134A Replacement Sensor
LC-R01 Replacement Reference Leak Source

 **CALRIGHT
INSTRUMENTS**

The Right Source For Your Test & Measurement Needs

8715 Mesa Point Terrace San Diego, CA 92154
Toll Free: 1.866.363.6634 Tel: 1.619.429.4545 Fax: 1.619.374.7012
Email: sales@calright.com <http://www.calright.com>