

IR Thermometer/Scanner IRTC50 with Starburst Laser Targeting

IRTC50

BEEKER

Ideal for: Energy Auditing, Home & Building Inspection and Maintenance, HVAC, Construction and Electrical Work

Scanning IRTs let you focus on the laser's target instead of the display reading. The color of the light panel (red, green or blue) and the speed of the beeper (fast, silent or slow) tell you—without looking at the display—whether the surface you're targeting is above, at or below the reference temperature ± the setpoint band.

Features:

Ioll Free: 1.866.363.6634 Tel: 1.619.429.4545 Fax: 1.619.374.7012

CA 92154

8715 Mesa Point Terrace San Diego, (

sal

Email:

- Choice of three setpoint bands in scanning mode: 1° (default), 5° or 10°F (0.5°, 3° or 5.5°C)
- Ideal for making relative measurements such as in energy auditing
- One long pull of the trigger automatically captures a reference temperature and launches scanning mode
- The Star Burst laser pattern helps determine the optimum distance to a target
- Large backlit LCD automatically holds its reading when the trigger is released
- 3% or better accuracy in conventional IRT mode
- To extend battery life, backlight shuts off after 15 seconds of inactivity and instrument powers off after 60 seconds
- °F/°C Switch



General Tools & Instruments 80 White Street, New York, NY 10013-3567 TEL: 212. 431. 6100 TOLL FREE: 800. 697. 8665 sales@generaltools.com www.generaltools.com IRTC50SS Printed in USA 2.5M 11/12





CE

RoHS

No. IRTC50

Audible and Visual Alerts

Star Burst Laser Targeting (Representational Only!)

Specifications:

Temperature Range: -40° to 428°F (-40° to 220°C) Accuracy:

Accuracy: $\pm 4^{\circ}$ F/C or $\pm 2\%$ of reading >32°F (0°C) $\pm 3^{\circ}$ F/C or $\pm 3\%$ of reading <32°F (0°C)

Display Resolution: 0.1° (F or C)

Distance to Spot Ratio: 8:1

Fixed Emissivity: at 0.95, covers 90% of applications

Repeatability: ±1.5°F (1°C)

Response Time: 0.5 seconds

Operating Temperature: 32° to 104° F (0° to 40° C)

Storage Temperature: -20° to 122°F (-29° to 50°C)

Operating Humidity: 10 to 90%

Dimensions: 5.31 x 1.65 x 6.81 in. (135 x 42 x 173mm)

Weight: 6.24 oz. (117g) without battery Power Source: 1 "9V" battery (included)

Includes:

1 "9V" Battery and User's Manual



The Star Bu determine ti to a target Large backl holds its rea is released 3% or bette conventiona To extend b shuts off aff of inactivity

17 O OWIGH

1