

**GENERAL®**

# Pin/Pinless Deep Sensing Moisture Meter

w/ Spherical Sensor and Remote Probe

**Ideal for contractors, woodworkers and homeowners to measure the moisture content of wood and other construction materials**

## Features & Benefits:


- Two measurement modes: Pin and pinless
- Pin mode uses replaceable pins at end of 46 in. cable; pinless mode uses integral ball sensor with up to 4 in. measurement depth
- Optional MP905 deep wall moisture probe is available (see reverse side)
- Displays % WME or relative readings simultaneously on two displays: 0 to 99.9 count jumbo LCD, and 40-dot tri-color LED Bargraph
- Spare pins storage compartment
- Auto-calibrating
- Data hold function
- Low battery warning
- User can set beeper sound, auto power off time, backlight function
- Superior to flat bottom sensors by enabling the user to measure in corners, hard-to-reach areas and narrow spaces
- Small contact area for improved repeatability
- Spherical sensor works on uneven surfaces and corners
- Works at any angle
- Can accommodate wide viewing angle
- Keeps hand away from sensing area, reducing interference



**Locate moisture/water damage deep behind tiles**



**The MMD950 with the optional MP905 Deep Wall Moisture Probe**



**No. MMD950**



8715 Mesa Point Terrace San Diego, CA 92154  
Toll Free: 1.866.363.6634 Tel: 1.619.429.4545 Fax: 1.619.374.7012  
Email: [sales@calright.com](mailto:sales@calright.com) <http://www.calright.com>

**CALRIGHT INSTRUMENTS**

The Right Source For Your Test & Measurement Needs



# Pin/Pinless Deep Sensing Moisture Meter

w/ Spherical Sensor  
and Remote Probe

## Specifications:

### Measurement Range:

6.0 to 87.6% WME (Wood Moisture Equivalent)  
and 0.1 to 99.9 REL

### Measurement Accuracy:

±3% of reading + 5 digits in pin mode

### Pin Length/Type:

10mm (0.4 in.) on remote probe;  
10mm and 15mm (spares)

**External Probe Cable Length:** 46 in. (1.168m)

**Spherical Ball Sensor Measurement Depth:**  
4 in. (101.6mm)

**Ball Sensor Diameter:** 1 in. (25.4mm)

**LCD Digit Height:** 0.9 in. (22.9mm)

**LCD Resolution:** 0.1%

### LED Bargraph Composition/Colors:

40 dots/green, red, yellow

**Operating Current:** 70 mADC max

### Operating Temperature:

32° to 122°F (0° to 50°C)

### Dimensions:

9 x 2.75 x 1.625 in. (229 x 70 x 41mm)

**Weight:** 8 oz. (249g)

**Power Source:** 1 "9V" battery (included)

## Includes:

Remote Probe, 1 "9V" Battery, 2 Sets of Spare  
Pins, Hard Carrying Case, User's Manual  
and 1 Year Limited Warranty

## Optional Accessory:

### Deep Wall Moisture Probe:

Length of Twin Probes with Replaceable  
Screw-in Tips: 5 in. (127mm)

Diameter of Probes: 0.14 in. (3.6mm)

Probe Hardness: 60 HRC  
(Hardness Rockwell "C" scale)

Length of Probe Cable: 56 in. (1.4m)



No. MMD950



Check for moisture damage deep  
below carpet surface



Locates moisture under  
bathroom floors



Locates moisture under bathroom  
vanities where mold thrives



Check for moisture in masonry

8715 Mesa Point Terrace San Diego, CA 92154  
Toll Free: 1.866.363.6634 Tel: 1.619.429.4545 Fax: 1.619.374.7012  
Email: sales@calright.com http://www.calright.com

**CALRIGHT**  
**INSTRUMENTS**  
The Right Source For Your Test & Measurement Needs



General Tools & Instruments

80 White Street, New York, NY 10013-3567

TEL: 212.431.6100 TOLL FREE: 800.697.8665

sales@generaltools.com www.generaltools.com

MMD950SS Printed in USA 02/14