

## DRS220 & DRSCM (Sold Separately) Digital Refrigerant Scale & Charging Module



- DRS220**
- Measures Weight in kgs and lbs
  - Refrigerant Tank Capacity Indicator
- DRSCM**
- Option for automated system charging
  - Set, start and allow the DRSCM to monitor progress
  - Valve closes to stop the flow of refrigerant when target is met

- Large, high-visibility LCD display
- Built-in memory remembers all previous settings
- Rugged, Compact Design
- Long Battery Life
- High Accuracy and Resolution
- Programmable
- Can be calibrated in the field with inexpensive reference weight
- 1 Year limited warranty

4 (AAA) Batteries, Manual

## HA1 Hermetic Compressor Analyzer



- 3 ranges of 250 VAC starting capacitors between 88-301 MFD
- Dual voltage operation of 120/240 VAC

- Indicates continuity and ground faults in motor windings with LED lights
- Free locked rotors by reversing motor action
- Convenient breakout jacks for measuring voltage and resistance
- 1 Year limited warranty

Adapter Cord (ACF1)

## DRS220 & DRSCM

<b>Capacity</b>	100 kilograms (220 Pounds) (2kPa, 0.02bars,mmHg)
<b>Accuracy</b>	0.5% of Reading ± 1 Least Significant Digit
<b>Resolution</b>	2g, 0.005 lbs., 0.1 oz.
<b>Power</b>	4 x 1.5V 'AAA' Alkaline Batteries (6 VDC)
<b>Battery Life</b>	30 hours continuous use 9V Alkaline Battery
<b>Operating Temperature</b>	0°C – 60°C (32°F – 140°F)
<b>Dimensions</b>	10.5" x 10.5" x 1.75"
<b>Weight</b>	2.5 kg (5.5 lbs.)

**DRS220**  
Digital Micron Scale



**DRSCM**  
Digital Charging Module



**CALRIGHT INSTRUMENTS**

The Right Source For Your Test & Measurement Needs

8715 Mesa Point Terrace San Diego, CA 92154  
Toll Free: 1.866.363.6634 Tel: 1.619.429.4545 Fax: 1.619.374.7012  
Email: sales@calright.com <http://www.calright.com>