



## ***Refrigerant Leak Detector***



### **Functions**

- Sensitive to .5 oz per year R134A, R123, R410A
- Automatically detects all existing halogenated refrigerants and blends

### **Features**

- Two position sensitivity selector
- Audible tick and visual indicators identify refrigerant leak rate
- Auto zeros when turned on
- 18 1/2" Long gooseneck probe
- Colored LED leak indication
- 1-Year limited warranty

### **Applications**





### Includes

- Battery (9V)
- Manual (RLD10-MAN)

### Specifications

Sensor	Advanced ionization detection
Sensitivity	0.5 oz. per year R134A
Power Supply	9V battery
Battery Life	8 continuous hours
Warm Up Time	< 10 seconds
Response Time	< 1 second
Duty Cycle	Continuous
Probe Length	18 ½"
Dimensions	8" x 4" x 1 ½"
Weight	14.1 oz
Operating Conditions	32 ° to 120 °F (0 ° to 49 °C) 0 to 80% RH (non-condensing)
Refrigerants Detected	R11, R12, R13, R22,R23, R113, R114 R134A, R500, R502, Halons, R404A, SF6, Perchloroethylene, Blends, R410A

### Downloads



**Manual**



**Data Sheet**



Made in TAIWAN