

Functions

Features

Includes

Specifications

Sensor	Advanced ionization detection
Sensitivity	.5 oz. per year R134A
Power Supply	9V battery
Battery Life	8 continuous hours
Warm Up Time	< 10 seconds
Response Time	< 1 second
Duty Cycle	Continuous
Probe Length	18 1/2"
Dimensions	8" x 4" x 1 1/2"
Weight	14.1 oz (400g)
Operating Conditions	32° to 120°F (0° to 49°C)
Refrigerants Detected	0 to 80% RH (noncondensing) R11, R12, R13, R22,R23, R113, R114 R134A, R500, R502 Halons R404A SF6 Perchloroethylene Blends R410A

Replacement Parts & Accessories

Sensor Cap	RLDTG (RLD10)
Sensor	RLDSENS (RLD10)
Sensor	RLD15SENS (RLD15)
Sensor Filter (5 pack)	RLDTF (RLD15)
Leak Test Vial	RLDLS (RLD15)



RLD10 Refrigerant Leak Detector

- Detects Industry Standard Refrigerants Including but not limited to:
R11 R12, R13, R22,R23, R113 R114 R134A, R500, R502 Halons R404A SF6 Perchloroethylene Blends R410A

- Auto zeros when turned on
- Two position sensitivity selector
- LED panel indicates refrigerant leak concentration
- Audible tick rate
- Long gooseneck probe
- One-hand operation
- Automatically detects all existing refrigerant and blends
- 1 Year limited warranty

1 (9V) Battery, Manual

RLD15 Refrigerant Leak Detector

- Detects Industry Standard Refrigerants Including but not limited to:
HFC: R-134a, R-410A, R-404A, R-407C, R-507, (R-134a, R410A sensitivity ≥ 0.05 oz./yr)
HCFC:R-22 (R-22 sensitivity ≥ 0.025 oz./yr)
CFC:R-12 Hydrocarbon Blends: HC-12a®, OZ-12a®

- Solid Electrolyte Semiconductor Sensor Technology
- Digital Numeric Leak Size Indicator
- 3 Sensitivity Levels
- Visual LED Leak Alarm
- Whisper Action Pump
- Automatic Calibration & Ambient Level Reset
- Splash Resistant
- 3 Year limited warranty (Includes Sensor)

(5) RLDTF, RLDLS, Batteries 4(AA), Hard Carrying Case, Manual