

# TSN

#### **Cam-Over Torque Wrench Internally Preset**

		Torque Ranges		
Model	Item #	lbf.ft	N.m	kgf.m
TSN25D	020250	2 - 18	3 - 25	0.3 - 2.5
TSN25A	020249	2 - 18	3 - 25	0.3 - 2.5
TSN55	020251	10 - 40	15 - 55	1.5 - 5.6
TSN125	020252	30 - 90	40 - 125	4 - 12.7

## inches DIMENSIONS AND WEIGHT

Length			We	eight	
Model	in.	mm	Square Drive	lbs.	kg.
TSN25D	8 1/2	216	1/4"	0.75	0.34
TSN25A	8 1/2	216	3/8"	0.75	0.34
TSN55	12 3/4	324	3/8"	1.75	0.80
TSN125	18 1/0	460	1/2"	3.0	1.36



#### NOTE!

For Signal Output (Electric Signal) models, see page 02.16 For Insulated TSN wrenches see page 02.17

For Left-hand, Pin-Retention & CW Direction Only Models available upon request. (See Website www.mountztorque.com)

prevents tampering.

Non-length dependent.

A preset production torque wrench.

Fully supported non-strip ratchet head.

ESD compliant (TSN25 models only).

### TSN HEAD PROTECTION COVERS

Strong corrosion-resistant stainless steel head, protective coated handle and non-slip rubber grip. Features a mechanical torque adjustment locking device (M-TALD). An auto locking single key operation

The wrench "slips" free when preset torque is reached, thus eliminating overtorquing.

Tamper-proof internal adjustment. No external adjustment scale - must be preset using a torque analyzer.

This rubber cover fits the head and protects the work piece from accidental damage from the tool during use. Ideal for production areas, like automotive industry.

Model	Item #
TSN25	020183
TSN55	020184
TSN125	020185



#### HANGING LOOP

Replace end cap of TSN with a "Loop" end cap for hanging the wrench safely when it's not being used. Sold separately.

Model	Item #
TSN25D	020588
TSN25A	020588
TSN55	020590
TSN125	020589

CALRICHT
INSTRUMENTS

The Right Source For Your Test & Measurement Needs

8715 Mesa Point Terrace San Diego, CA 92154
Toll Free: 1.866.363.6634 Tel: 1.619.429.4545 Fax: 1.619.374.7012
Email: sales@calright.com http://www.calright.com