



# M110A

## Analog Multimeter

### MAINTAIN AND TROUBLESHOOT HVAC/R SYSTEMS

- 21 ranges
- 600 Volts AC & 300 Volts DC
- DC millivolts
- Flame safeguard testing
- Resistance




# M110A • Analog Multimeter

The M110A, in addition to high-resolution voltage and ohms scales needed for electrical troubleshooting also includes the features that help you maintain and troubleshoot HVAC/R systems. Features like DC millivolts and microamps let you troubleshoot flame safeguard circuits and the millivolts function helps you evaluate heat anticipators.

## The M110A has the following features:

- 21 ranges
- 600 Volts AC and 300 Volts DC
- 2 Megohm resistance
- High resolution DC  $\mu$ A for flame safeguard testing
- DC millivolt scale allows use of adapters
- Color-coded and mirrored scale plate
- Three year limited warranty



## Specifications

Ranges	
DC Millivolts	0 - 60, 300, 1200m V
DC Volts	0 - 3, 12, 60, 300, 1200 V (0 - 12,000 V with optional probe)
DC Microamps	0 - 30, 60 $\mu$ A
DC Millamps	0 - 60, 600m A
OHMS	0 - 200Ω, 2K, 20K, 2M
AC Volts	0 - 6, 30, 60, 300, 600 V
Temperature	0 - 60, 300, 500°F
Accuracy	
DC	$\pm 3\%$ of full scale
OHMS	$\pm 3\%$ of scale length
AC	$\pm 4\%$ of full scale
Temperature	$\pm 2$ divisions
General	
Input Impedance	30K/V DC, 15K/V AC
Batteries	Two 1.5V, size "AA" (NEDA #15D) batteries One 9 V (NEDA #1604) battery
Fuse	6/10A (0.5 ohm internal resistance) 3AG series Note: To maintain calibration accuracy and instrument protection, replacement fuse must be of the proper current and resistance value.

## Optional Accessories:

Battery 1.5V, size "AA"	AB1
Battery 9V	AB9
Fuse 6/10A, 0.5Ω (pkg. of 3)	AF10
Test leads, (set)	ATL50
Test leads, rubber (set)	ATL25
Alligator clip adapters, insulated (pr)	AAC
High voltage probe (12K V DC)	A12K
Carrying case	AC110
Temperature adapter	TA2K

Distributed By:



1-800-547-5740 • Fax: (503) 643-6322  
www.ueitest.com • Email: info@ueitest.com

## IN CANADA

Vancouver: Phone: 1-877-475-0648 • (604) 278-4511 • Fax: (604) 278-8299  
Toronto: Phone: 1-877-475-0648 • Fax: (905) 238-5117

## IN EUROPE

Phone: +44 1707 375550 • Fax: +44 1707 393277

