

Ultrasonic Thickness Gauge with Thru Coating Capabilities

26



UTG-2600 comes complete with Certificate of Calibration, Operation Manual and Custom Carry Case.

Display type	4-digit LCD w/ Back Light
Minimum display unit	0.003 (if > 3.93" 0.0003" (if < 3.93")
Measuring Range	Standard Mode: 0.03-8.0" in steel Thru Coating Mode: 0.118" - .905" 3.0 - 23mm) w/ standard probe
Accuracy	+/- 1% xH + 0.0007" (H=displayed value)
Sound velocity range	3280-32805 ft/ s (1000-9999m/ s)
Upper/ Lower Limit Preset Alarm	Yes
Operating temperature	32-122 degrees F
Frequency	4MHz
Update range	4Hz
Memory	500 Test Values
Output	RS 232
Power supply	3v AA alkaline batteries (2pc)
Battery life	Approx. 100 hours (w/ backlight off)
Power consumption	Working current is less than 3V
Dimensions	5.86" x 2.87" x 1.25" (149 x 73 x 32mm)
Weight	5.6oz (160g)

UTG-2600

\$ 1,195

State of the art, digital tester is capable of reading wall thickness thru coatings and paint without affecting the measurement and is packed with the most popular features including basic measurement, Scanning Capabilities, Adjustable Sound Velocity, extended memory and RS 232 output capabilities. This dynamic sonic gauge is designed to measure the thickness of metallic and non-metallic materials such as steel, aluminum, titanium, plastics, ceramics, glass and any other good ultrasonic wave conductor as long as it has parallel top and bottom surfaces. The UTG-2600 will accurately display readings in either inch or millimeter after a simple calibration to a known thickness or sound velocity.



The Right Source For Your Test & Measurement Needs

2232 Verus Street Suite D San Diego CA 92154 USA
Toll Free: 866.363.6634 Tel: 619.429.4545 Fax: 619.374.7012
Email: sales@calright.com <http://www.calright.com>