

HIOKI

DIGITAL M HiTESTER

3454-11, -51 (3-range), 3454-10 (4-range)

Field measuring instruments



with
200mA
continuity

Insulation Testing- The Next Generation



ISO 9001
JMI-0216



ISO 14001
JQA-E-90091

CALRIGHT
INSTRUMENTS

The Right Source For Your Test & Measurement Needs

2232 Verus Street Suite D San Diego CA 92154 USA
Toll Free: 866.363.6634 Tel: 619.429.4545 Fax: 619.374.7012
Email: sales@calright.com <http://www.calright.com>



3454-51
No CE marking



3454-10

3-range or 4-range INSULATION & CONTINUITY 200 mA

New!
Sliding Cover
System



Insulation measurement through sight and sound!

The reference value is set separately for each measurement range.

Function	Reference value (3454-11 & 3454-51)
Insulation	250 V/500 V --- 0.2/0.4/0.5/1/2/3/5/10/20/30/50/100/200 (MΩ)
	1000 V --- 1/2/3/5/10/20/30/50/100/200/500/1000/2000 (MΩ)
Continuity	0.5/1/2/3/4/5/6/10/20/30/50/100/200/1k (Ω)



Insulation Ω: Meas. value < Ref. value FAIL, Ref. value ≤ Meas. value PASS
 Continuity: Meas. value ≤ Ref. value PASS, Ref. value < Meas. value FAIL
 Buzzer can be set to sound on either PASS or FAIL

Ex. Insulation resistance

Buzzer on FAIL at 20 MΩ or less

Ex. Continuity

Buzzer on PASS at 10 Ω or less



Back-lighting liquid crystal display for easy reading in dark areas.

Compact storage without disconnecting test probes

Checks ground wire continuity with a short current of 200 mA

Also capable of testing the continuity of electrical facility grounds in accordance with IEC 60364.

3454 series specifications

Accuracy at 23°C±5°C (73°F±9°F), 90% rh or less

MODEL	3454-11 & 3454-51			3454-10				
	Insulation test voltage	250 V DC	500 V DC	1000 V DC	50 V DC	125 V DC	250 V DC	500 V DC
Insulation resistance	Measurement range* 1	4.000 / 40.00 / 400.0 / 500 / 4000(1000 V range only) MΩ			4.000 / 40.00 / 200.0 MΩ		4.000 / 40.00 / 400.0 / 2000 MΩ	
	1st effective range	0.200 to 50.0 MΩ		0.200 to 200.0 MΩ	0.200 to 10.00 MΩ		0.200 to 100.0 MΩ	
	2nd effective range	0 to 0.199 / 50.1 to 500 MΩ		0 to 0.199 / 200.1 to 4000 MΩ	0 to 0.199 / 10.01 to 200.0 MΩ		0 to 0.199 / 100.1 to 2000 MΩ	
	Accuracy	1st effective range: ±3 %rdg, ±4 dgt. / 2nd effective range: ±5 %rdg, ±5 dgt.						
	Voltage with no load	Not more than 1.2 □ rated measurement voltage						
	Short circuit current	1.2 mA max.						
	Response time	∞ to center, ∞ to 0 MΩ within 5 s (within accuracy range)						
Low resistance (continuity)	Measurement range: 40.00 / 400.0 / 4.000 k / 40.00 k / 400.0 k / 4.000 MΩ Short circuit current: 200 mA Accuracy: ±3 %rdg, ±6dgt. (±5 %rdg, ±6dgt. at 400 kΩ range or higher), Open terminal voltage: 4 to 6 V, Response time: 5 s max.							
AC voltage	Display indication range : 0 to 750 V, Accuracy: ±3 %rdg, ±6 dgt.(up to 600V), Frequency range: 50 / 60 Hz, Input impedance: 100 k							

*1. Measurement range shifts automatically.

- Other functions: Insulation and low resistance mode - comparator, measurement value hold; Insulation resistance mode - auto discharge; Insulation and AC voltage mode - live wire warning (when voltage of 70V ±10V exists across measurement terminals); Low resistance mode - zero adjust; All measurement modes - battery indicators, auto power save
- Display: Semi-transparent LCD, "4000" count
- Display update rate: 2 times / second
- Load protection(10 s): Insulation resistance mode - 600 Vrms (1000 V range; 1200 Vrms); AC voltage mode - 800 Vrms; Low resistance / continuity mode - 600 Vrms(fuse protection)
- Safety standard: EN61010-1 CAT III 600 V
- EMC standard: EN61326
- Ambient temperature range for use: 0 to 40°C (32°F to 104°F), 90% rh or less (no condensation)
- Ambient temperature range for storage: -20 to 50°C (-4°F to 122°F), 90% rh or less (no condensation)
- Power source: R6P manganese battery □ 4 or LR6 alkaline battery □ 4
- Dimensions and Mass: Approx. 175 (6.9") W □ 148 (5.9") H □ 56 (2.3") D mm; Approx. 530 g (18.7 oz.) (with display cover closed)

DIGITAL M HiTESTER 3454-11, 3454-10

(Includes TEST PROBE 9294 and Strap band)

*DIGITAL M HiTESTER 3454-51

(Includes * TEST PROBE 9289, *Alligator clips and Strap band) *No CE marking

Accessories

for 3454-11, -10



Lead length approx. 1.2 m (47.2")

TEST PROBE 9294


for 3454-51



Lead length approx. 1.2 m (47.2")

* TEST PROBE 9289 with attachable alligator clips

Options



* BREAKER PIN 9288
To be attached on top of 9294 (Red)



Lead length approx. 1.3 m (51.1")

CONNECTION CORD 9257
*No CE marking

DISTRIBUTED BY

CALRIGHT INSTRUMENTS

The Right Source For Your Test & Measurement Needs

2232 Verus Street Suite D San Diego CA 92154 USA
Toll Free: 866.363.6634 Tel: 619.429.4545 Fax: 619.374.7012
Email: sales@calright.com http://www.calright.com