

Keysight 33250A

Function/Arbitrary Waveform Generator

Data Sheet



Product Discontinuance Notice

The 33250A function generator and all associated options will be discontinued December 1, 2016. The last date this product can be ordered is November 30, 2016.

- For new product purchases, Keysight recommends the 33600A Trueform Series waveform generators.
- For more information, as well as to access to detailed migration guides, please visit www.keysight.com/find/nextgenFGs
- To contact a product selection expert, visit www.keysight.com/find/contactus

Standard Waveforms

The Keysight Technologies, Inc. 33250A function/arbitrary waveform generator uses direct digital-synthesis techniques to create a stable, accurate output on all waveforms, down to 1 μ Hz frequency resolution. The benefits are apparent in every signal you produce, from the sine wave frequency accuracy to the fast rise/fall times of square waves, to the ramp linearity.

Front-panel operation of the 33250A is straightforward and user friendly. The knob or numeric keypad can be used to adjust frequency, amplitude and offset. You can even enter voltage values directly in Vpp, Vrms, dBm, or high/low levels. Timing parameters can be entered in hertz (Hz) or seconds.

- 80 MHz sine and square wave outputs
- Sine, square, ramp, noise and other waveforms
- 50 MHz pulse waveforms with variable rise/fall times
- 12-bit, 200 MSa/s, 64K-point deep arbitrary waveform

Custom Waveform Generation

Why settle for a basic function generator when you can get arbitrary waveforms at no extra cost? With the 33250A, you can generate arbitrary waveforms with 12-bit vertical resolution, 64K memory depth, and a sample rate of 200 MSa/s. You can also store up to four 64K-deep arbitrary waveforms in non-volatile memory with user-defined names to help you find the right waveform when you need it most.

The included Keysight IntuiLink software allows you to easily create, edit, and download complex waveforms using the IntuiLink arbitrary waveform editor. Or you can capture a waveform using IntuiLink oscilloscope or DMM and send it to the 33250A for output. For programmers, ActiveX components can be used to control the instrument using SCPI commands. IntuiLink provides the tools to easily create, download, and manage waveforms for your 33250A. To find out more about IntuiLink, visit www.keysight.com/find/intuilink.

Pulse Generation

The 33250A can generate simple pulses up to 50 MHz. With variable edge time, pulse width and voltage level, the 33250A is ideally suited to a wide variety of pulse applications.

Built-in Versatility

AM, FM and FSK capabilities make it easy to modulate waveforms with or without a separate source. Linear or logarithmic sweeps can be performed with a programmable frequency marker signal. Programmable burst count and gating allow you to further customize your signal.

For system applications, both GPIB and RS-232 interfaces are standard, and support full programmability using SCPI commands.

Color Graphical Display

The unique design of the 33250A combines a low-profile instrument with the benefits of a color graphical display. Now you can display multiple waveform parameters at the same time. The graphical interface also allows you to modify arbitrary waveforms quickly and easily.

Timebase Stability and Clock Reference

The 33250A TCXO timebase gives you frequency accuracy of 2 ppm for your most demanding applications. The external clock reference input/output lets you synchronize to an external 10 MHz clock, to another 33250A, or to another Keysight 332XXA function/arbitrary waveform generator. Phase adjustments can be made from the front panel or via a computer interface, allowing precise phase calibration and adjustment.

Measurement Characteristics

Waveforms	
Standard	Sine, square, pulse, ramp, noise, sin(x)/x, exponential rise, exponential fall, cardiac, DC volts
Arbitrary	
Waveform length	1 to 64K points
Amplitude resolution	12 bits (including sign)
Repetition rate	1 μ Hz to 25 MHz
Sample rate	200 MSa/s
Filter bandwidth	50 MHz
Non-vol. memory	Four (4) 64K waveforms

Frequency characteristics	
Sine	1 μ Hz to 80 MHz
Square	1 μ Hz to 80 MHz
Pulse	500 μ Hz to 50 MHz
Arb	1 μ Hz to 25 MHz
Ramp	1 μ Hz to 1 MHz
White noise	50 MHz bandwidth
Resolution	1 μ Hz; except pulse, 5 digits
Accuracy (1 year)	2 ppm, 18 to 28 $^{\circ}$ C 3 ppm, 0 to 55 $^{\circ}$ C

Sinewave spectral purity		
Harmonic distortion		
	≤ 3 Vpp ¹	> 3 Vpp
DC to 1 MHz	-60 dBc	-55 dBc
1 to 5 MHz	-57 dBc	-45 dBc
5 to 80 MHz	-37 dBc ²	-30 dBc ²

Total harmonic distortion	
DC to 20 kHz	$< 0.2\% + 0.1$ mVrms
Spurious (non-harmonic) ³	
DC to 1 MHz	-60 dBc
1 to 20 MHz	-50 dBc
20 to 80 MHz	-50 dBc + 6 dBc/octave

Phase noise (30 kHz band)	
10 MHz	< -65 dBc (typical)
80 MHz	< -47 dBc (typical)

Signal characteristics	
Squarewave	
Rise/fall time	< 8 ns ⁴
Overshoot	$< 5\%$
Asymmetry	1% of period + 1 ns
Jitter (rms)	
< 2 MHz	0.01% + 525 ps
≥ 2 MHz	0.1% + 75 ps
Duty cycle	
≤ 25 MHz	20.0 to 80.0%
25 to 50 MHz	40.0 to 60.0%
50 to 80 MHz	50.0% (fixed)
Pulse	
Period	20.00 ns to 2000.0 s
Pulse width	8.0 ns to 1999.9 s
Variable edge time	5.00 ns to 1.00 ms
Overshoot	$< 5\%$
Jitter (rms)	100 ppm + 50 ps

Signal characteristics (Continued)	
Ramp	
Linearity	$< 0.1\%$ of peak output
Symmetry	0.0 to 100.0%
Arb	
Minimum edge time	< 10 ns
Linearity	$< 0.1\%$ of peak output
Settling time	< 50 ns to 0.5% of final value
Jitter (rms)	30 ppm + 2.5 ns

Output characteristics	
Amplitude (into 50 Ω)	10 mVpp to 10 Vpp ⁵
Accuracy (at 1 kHz, >10 mVpp, Autorange on)	$\pm 1\%$ of setting ± 1 mVpp
Flatness (sinewave relative to 1 kHz, Autorange on)	
< 10 MHz	$\pm 1\%$ (0.1 dB) ⁶
10 to 50 MHz	$\pm 2\%$ (0.2 dB)
50 to 80 MHz	$\pm 5\%$ (0.4 dB)
Units	Vpp, Vrms, dBm, high and low level
Resolution	0.1 mV or 4 digits

Offset (into 50 Ω)	± 5 Vpk ac + dc
Accuracy	1% of setting + 2 mV + 0.5% of amplitude

Waveform output	
Impedance	50 Ω typical (fixed) > 10 M Ω (output disabled)
Isolation	42 Vpk maximum to earth
Protection	Short-circuit protected ⁷ ; overload relay automatically disables main output

Modulation characteristics	
AM	
Carrier waveforms	Sine, square, ramp, and arb
Mod. waveforms	Sine, square, ramp, noise, and arb
Mod. frequency	2 mHz to 20 kHz
Depth	0.0 to 120.0%
Source	Internal/external

FM	
Carrier waveforms	Sine, square, ramp, and arb
Mod. waveforms	Sine, square, ramp, noise, and arb
Mod. frequency	2 mHz to 20 kHz
Peak deviation	DC to 80 MHz
Source	Internal/external

FSK	
Carrier waveforms	Sine, square, ramp, and arb
Mod. waveform	50% duty cycle square
Internal rate	2 mHz to 100 kHz
Frequency range	1 μ Hz to 80 MHz
Source	Internal/external

External modulation input	
Voltage range	± 5 V full scale
Input impedance	10 Ω
Frequency	DC to 20 kHz
Latency	< 70 μ s typical

Measurement Characteristics (Continued)

Burst	
Waveforms	Sine, square, ramp, pulse, arb, and noise
Frequency	1 μ Hz to 80 MHz ⁹
Burst count	1 to 1,000,000 cycles or infinite
Start/Stop phase	-360.0 to +360.0°
Internal period	1 ms to 500 s
Gate source	External trigger
Trigger source	Single manual trigger,
Trigger delay	
N-cycle, infinite	0.0 ns to 85.000 sec

Sweep	
Waveforms	Sine, square, ramp, and arb
Type	Linear and logarithmic
Direction	Up or down
Start F/Stop F	100 μ Hz to 80 MHz
Sweep time	1 ms to 500 s
Trigger	Single manual trigger, internal, external trig
Marker	Falling edge of sync signal (programmable)

System characteristics

Configuration times (typical)⁹

Function change	
Standard	100 ms
Pulse	660 ms
Built-in arb	220 ms
Frequency change	20 ms
Amplitude change	50 ms
Offset change	50 ms
Select user arb	< 900 ms for < 16K pts.
Modulation change	< 200 ms

Arb download times GPIB/RS-232 (115Kbps)

Arb Length	Binary	ASCII Integer	ASCII Real
64K points	48 sec	112 sec	186 sec
16K points	12 sec	28 sec	44 sec
8K points	6 sec	14 sec	22 sec
4K points	3 sec	7 sec	11 sec
2K points	1.5 sec	3.5 sec	5.5 sec

Trigger characteristics

Trigger input	
Input level	TTL compatible
Slope	Rising or falling, (selectable)
Pulse width	> 100 ns
Input impedance	10 k Ω , DC coupled
Latency	
Burst	< 100 ns (typical)
Sweep	< 10 μ s (typical)
Jitter (rms)	
Burst	1 ns; except pulse, 300 ps
Sweep	2.5 μ s

Trigger output	
Level	TTL compatible into 50 Ω
Pulse width	> 450 ns
Maximum rate	1 MHz
Fanout	\leq 4 Keysight 33250A's (or equivalent)

Clock Reference

Phase Offset	
Range	-360 to +360°
Resolution	0.001°

External reference input

Lock range	10 MHz \pm 35 kHz
Level	100 mVpp to 5 Vpp
Impedance	1 k Ω nominal, accoupled
Lock time	< 2 s

Internal reference output

Frequency	10 MHz
Level	632 mVpp (0 dbm), nominal
Impedance	50 Ω nominal, accoupled

Sync output

Level	TTL compatible into > 1 k Ω
Impedance	50 Ω nominal

General

Power supply	100-240 V, 50-60 Hz 100-127 V, 50-400 Hz
Power consumption	140 VA
Operating temp.	0 to 55°C
Storage temp.	-30 to 70°C
Stored states	4 named user configurations
Power on state	Default or last
Interface	IEEE-488 and RS-232 std.
Language	SCPI-1997, IEEE-488.2
Dimensions (WxHxD)	
Bench top	254 x 104 x 374 mm
Rackmount	213 x 89 x 348 mm
Weight	4.6 kg
Safety designed to	EN61010-1, CSA1010.1, UL-311-1
EMC tested to	IEC-61326-1 IEC-61000-4-3 criteria B IEC-61000-4-6 criteria B
Vibration and shock	MIL-T-28800E, Type III, Class 5
Acoustic noise	40 dBA
Warm-up time	1 hour
Calibration interval	1 year

Ordering Information

Keysight 33250A

80 MHz function/arbitrary waveform generator

Accessories included

Operating manual, service manual, quick reference guide, IntuiLink waveform editor software, test data, RS-232 cable, and power cord (see language option).

Options

Opt. A6J	ANSI Z540 calibration
Opt. AB0	Taiwan: Chinese manual
Opt. AB1	Korea: Korean manual
Opt. AB2	China: Chinese manual
Opt. ABA	English: English manual
Opt. ABD	Germany: German manual
Opt. ABF	France: French manual
Opt. ABJ	Japan: Japanese manual

Other Accessories

34131A	Carrying case
34161A	Accessory pouch
34190A	Rackmount kit*

* For racking two 33250As side-by-side, order the following items:
Lock-link kit (34194A), Flange kit (34191A)

www.keysight.com/find/33250A

For more information on Keysight Technologies' products, applications or services, please contact your local Keysight office. The complete list is available at: www.keysight.com/find/contactus

Americas

Canada	(877) 894 4414
Brazil	55 11 3351 7010
Mexico	001 800 254 2440
United States	(800) 829 4444

Asia Pacific

Australia	1 800 629 485
China	800 810 0189
Hong Kong	800 938 693
India	1 800 112 929
Japan	0120 (421) 345
Korea	080 769 0800
Malaysia	1 800 888 848
Singapore	1 800 375 8100
Taiwan	0800 047 866
Other AP Countries	(65) 6375 8100

Europe & Middle East

Austria	0800 001122
Belgium	0800 58580
Finland	0800 523252
France	0805 980333
Germany	0800 6270999
Ireland	1800 832700
Israel	1 809 343051
Italy	800 599100
Luxembourg	+32 800 58580
Netherlands	0800 0233200
Russia	8800 5009286
Spain	800 000154
Sweden	0200 882255
Switzerland	0800 805353
	Opt. 1 (DE)
	Opt. 2 (FR)
	Opt. 3 (IT)
United Kingdom	0800 0260637

For other unlisted countries:
www.keysight.com/find/contactus
(BP-09-23-14)