

CLAMP METER

TECHNICAL DATA

FEATURES

- Autoranging mini clamp meter
- 4000-count LCD with backlight
- Data Hold and zero functions
- Diode test to 0.3m A and continuity buzzer
- Auto shut off and low battery indication
- 0.9" (23mm) jaw opening
- EN61010-1 600V Cat. III
- Complete with TL-88-1 test leads, AM-4 batteries and C-820 carrying case

SPECIFICATIONS

- AC Current Range: 40.00, 400.0 A
DC Current Range: 40.00, 400.0 A
AC Voltage Range: 400.0mV, 4.000, 40.00, 400.0, 600V
DC Voltage Range: 4.000, 40.00, 400.0, 600V
Resistance Range: 400.0 Ω , 4.000, 40.00, 400.0k Ω , 4.000, 40.00M Ω
Capacitance Range: 40.00, 400.0nF, 4.000, 40.00, 100 μ F
Frequency Range: 5.000, 50.00, 500.0Hz, 5.000, 50.00, 150.0kHz
Duty Cycle: 0.5 to 99.0%
Power Supply: 2 x "AAA " 1.5V batteries
Dimensions: 8.1 x 2.75 x 1.5" (205 x 70 x 37mm)
Weight: 7.1 oz (200g)

ORDERING INFORMATION

- ST-332 AC/DC Clamp Meter
CERTICM1 Accredited Calibration Certificate

