

CLAMP METER

TECHNICAL DATA

FEATURES

- Autoranging mini clamp meter
- Temperature measurement to 1832°F/ 1000° C
- 4000-count LCD with backlight
- Data Hold and zero functions
- Diode test to 0.3m A and continuity buzzer
- Auto shut off and low battery indication
- 0.9" (23mm) jaw opening
- EN61010-1 600V Cat. III
- Complete with AD-1 temperature input adapter, TP-01 type K thermocouple wire probe, TL-88-1 test leads, AM-4 batteries and C-820 carrying case

SPECIFICATIONS

- AC Current Range: 40.00, 400.0 A
DC Current Range: 40.00, 400.0 A
AC Voltage Range: 400.0mV, 4.000, 40.00, 400.0, 600V
DC Voltage Range: 4.000, 40.00, 400.0, 600V
Resistance Range: 400.0Ω, 4.000, 40.00, 400.0kΩ, 4.000, 40.00MΩ
Capacitance Range: 40.00, 400.0nF, 4.000, 40.00, 100μF
Frequency Range: 5.000, 50.00, 500.0Hz, 5.000, 50.00, 150.0kHz
Duty Cycle: 0.5 to 99.0%
Temperature Range: -58 to 1832°F (-50 to 1000° C)
Power Supply: 2 x "AAA " 1.5V batteries
Dimensions: 8.1 x 2.75 x 1.5" (205 x 70 x 37mm)
Weight: 7.1 oz (200g)



ORDERING INFORMATION

- ST-333 AC/DC Clamp Meter
CERTICM1 Accredited Calibration Certificate