

THE RIGHT SOURCE THE RIGHT SOLUTIONS

INFRAREDTHERMOMETER

TECHNICAL DATA

FEATURES

- Infrared thermometer with integral type K thermocouple input
- · Built-in laser pointer identifies target area
- 30:1 distance to spot size ratio
- Digitally adjustable emissivity from 0.10 to 1.0
- · Automatic emissivity capture
- High and low alarms
- Fahrenheit/ Celsius switchable
- Max, Min, Avg, Diff record
- 20 data points of memory
- Display backlighting
- · Auto data hold and auto shut off
- · Over range and polarity indications
- Trigger lock
- Includes type K thermocouple probe, battery, and carrying case

SPECIFICATIONS

Type K Temp. Range: -58.0 to 2498°F (-50.0 to 1370° C) Resolution: 0.1° C: -50 to 1370° C; 0.1°F: -58 to 1999.9°F;

1°F: 2000 to 2498°F

Accuracy: $\pm 1.5\%$ rdg. $+3^{\circ}$ C ($+5^{\circ}$ F): -50 to 1000° C (-58 to 1832° F); $\pm 1.5\%$ rdg. $+2^{\circ}$ C (3.6° F): 1000 to 1370° C (1832

to 2498°F)

IR Temp. Range: -50.0 to 1050.0° C (-58.0 to 1922.0°F)

Resolution: 0.1° C (0.1°F)

Accuracy: $\pm 5^{\circ}$ C ($\pm 9^{\circ}$ F): -50 to -20° C (-58 to -4°F); $\pm 1.5\%$ rdg. +2°C (+3.6°F): -20 to 200° C (-4 to 392°F); $\pm 2.0\%$ rdg. +2°C (+3.6°F): 200 to 538° C (392 to 1000°F); $\pm 3.5\%$ rdg.

 $+5^{\circ}$ C ($+9^{\circ}$ C): 538 to 1050° C (1000 to 1922°F)

Optical Resolution: 30:1

Emissivity: Digitally adjustable from 0.10 to 1.0

Spectral Response: 8 to 14µm

Laser: Class II, output < 1mW, wavelength 630~670nm

Response Time: Less than 1 second Power Supply: Single 9V battery

Dimensions: 3.9 x 2.2 x 9.0" (100 x 56 x 230mm)

Weight: 10.2 oz (290g)



ORDERING INFORMATION

ST-8835 Infrared Thermometer w/ Type K TC CERTIIR1 Accredited Calibration Certificate



2222 Verus Street Suite C San Diego CA 92154 USA Toll Free: 866.363.6634 Tel: 619.429.4545 Fax: 619.374.7012 Email: sales@calright.com http://www.calright.com